



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/030600 A1

(51) International Patent Classification⁷: B65D 33/25

(74) Agent: **HONG, Sung-Chul**; RM. 703, NewSeoul Bldg., 828-8,, Yeoksam-dong,, Kangnam-ku,, Seoul 135-080 (KR).

(21) International Application Number:
PCT/KR2004/002497

(22) International Filing Date:
25 September 2004 (25.09.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0067102
26 September 2003 (26.09.2003) KR

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(71) Applicant and

(72) Inventor: AHN, Ho Sung [KR/KR]; 208, Na-dong, Gunyeong Apt., Shingil 3-dong, Yeongdeungpo-gu, Seoul 150-053 (KR).

(54) Title: COMBINATION DEVICE WITH FASTENERS HAVING RIB AND GROOVE TRACKS



(57) Abstract: The object of this invention is to provide a fastening device with fasteners having rib and groove tracks which closes and seals a bag by alternative engagement of the tracks. In the present invention, to prevent an adhesive agent (27) from being exposed to impurities or the hands of a user, a predetermined amount of an adhesive agent (27) is evenly applied only to the groove track (23), (33) of each of a pair of fasteners (20) and (30) corresponding to each other, so that the groove track (23), (33) alternately and reliably engages with an associated rib track (25a), (26a), (35a), (35b). Therefore, the present invention overcomes the limitation of a material constituting the bag, thus being widely applied to various kinds of products, being convenient in use, achieving a slim structure, and providing an advantage from functional points of view.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*